

ELECTRONIC TUBE REFERENCE

25MP4

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Sixty-five-centimeter, 110-degree self-protected monochrome television picture tube with a tinted aluminized screen. Wide-angle deflection and integral protection support a large direct-view receiver display in a relatively shallow cabinet.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	22000 V
Published ratings and characteristics promoted where clearly stated; identical repeated sections compressed where applicable.	

65 cm 110-degree self-protected monochrome television picture tube with tinted aluminized screen.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1968 Mazda Belvu

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1968 MAZDA BELVU

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater or filament voltage	6.3 V	Published nominal value
Heater or filament current	600 mA	Published nominal value
Screen diagonal	65 cm	Published
Deflection angle	110 deg	Published