



ELECTRONIC TUBE REFERENCE

2C26A

Voltage - Triode (single high frequency) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

UHF triode pulse oscillator designed for grid-pulse or plate-pulse operation through approximately 300 MHz.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 1.1 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
TRANSCONDUCTANCE	0.0025 S
AMPLIFICATION FACTOR	16.3
MAXIMUM PLATE VOLTAGE	350 V
MAXIMUM PLATE DISSIPATION	10 W
Published ratings and characteristics promoted where clearly legible in the approved source.	

Ultra-high-frequency triode pulse oscillator designed for grid-pulse or plate-pulse service through 300 MHz.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1944 Hytron

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1944 HYTRON

Section 1 · Triode

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum Frequency	300 MHz	Pulse oscillator

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker