



ELECTRONIC TUBE REFERENCE

2G402A

Rectifier - Half Wave electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
RECTIFIER

Directly heated xenon-filled half-wave rectifier for high-voltage and mobile power supplies. Rated for approximately 10 kV peak inverse voltage, 250 mA DC output, and 1 A peak current.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	4
NOMINAL HEATER	2.5 V / 5 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Rectifier	
PEAK INVERSE VOLTAGE	10000 V
NOMINAL OUTPUT CURRENT	250 mA
PEAK FORWARD CURRENT	1 A
FORWARD VOLTAGE DROP	14 V
Extracted semantically from complete approved datasheet.	

Xenon-filled half-wave rectifier for high-voltage/mobile service.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1946 Standard Telephone and Cables

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1946 STANDARD TELEPHONE AND CABLES

Section 1 · Rectifier

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Supply frequency	50 Hz	ChokeInputFilter
Minimum cathode heating time	10 s	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker