

ELECTRONIC TUBE REFERENCE

2G5

Tuning Indicator electronic tube

CONSOLIDATED TECHNICAL DATA

2 SECTIONS

CONSTRUCTION

TRIODE-TUNING INDICATOR

Circular fluorescent tuning indicator incorporating an internally connected remote-cutoff triode amplifier.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	7
NOMINAL HEATER	2.5 V / 800 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
MAXIMUM PLATE VOLTAGE	250 V
Published promoted fields populated from Maximum Ratings / Characteristics / Typical Operation headings.	
SECTION2 Tuning Indicator	
No fixed ratings recorded.	

Circular fluorescent-target tuning indicator with an internally connected remote-cutoff triode amplifier.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1961 Tung Sol

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1961 TUNG SOL

Section 1 · Triode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Target Voltage Maximum	250 V	—
Target Voltage Minimum	100 V	—

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Target Current	4 mA	TargetVoltage=250V