

ELECTRONIC TUBE REFERENCE

3AGP16

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Compact P1 cathode-ray display tube with electrostatic focusing, magnetic deflection, and an aluminized screen; phosphor characteristics provide the persistence and fluorescence appropriate to the P1 variant.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 300 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray
No fixed ratings recorded.
Cathode-ray display/electron-gun section.

The Du Mont 3AGP16 is a three-inch aluminized radar CRT designed for miniature equipment with a low-current heater and approximately 70-degree magnetic deflection. This variant uses a P16 screen with violet fluorescence and extremely short persistence.



SOURCE OPERATING CONDITIONS

1960 Du Mont

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 DU MONT

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	—
Heater Current	300 mA	—
Focusing Method	Electrostatic text	—
Deflection Method	Magnetic text	—
Phosphor	P16 text	—
Fluorescence	Violet text	—
Persistence	Extremely short text	—
Deflection Angle	70 deg	Approximate
Screen Construction	Aluminized text	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker