

ELECTRONIC TUBE REFERENCE

3AI09A

Voltage - Triode (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
TRIODE

Telephone repeater triode for professional communications amplification.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	4
NOMINAL HEATER	4 V / 250 mA	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
PLATE RESISTANCE	12000 Ω
TRANSCONDUCTANCE	0.0005 S
AMPLIFICATION FACTOR	6
MAXIMUM PLATE VOLTAGE	190 V

Low-resistance directly heated repeater triode; A version uses an American 4-pin bayonet base.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1947 Standard Valves

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1947 STANDARD VALVES

Section 1 · Triode

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
GridToAnodeCapacitance	9 pF	—
GridToCathodeOrFilamentCapacitance	6 pF	—
AnodeToCathodeOrFilamentCapacitance	3.6 pF	—