

ELECTRONIC TUBE REFERENCE

3BRP2

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

CATHODERAY

Three-inch high-resolution flat-face dual-beam oscilloscope CRT with post-acceleration and precise beam-tracking accuracy. Its P2 blue-green/green, long persistence screen supports simultaneous comparative oscillographic traces.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray
No fixed ratings recorded.
Representative of two equivalent electron-beam display systems.

The Du Mont 3BRP2 is a high-resolution flat-face dual-beam CRT with post-acceleration and precise tracking accuracy. This variant uses a P2 screen with blue-green/green fluorescence and long persistence.

SOURCE OPERATING CONDITIONS

1960 Du Mont

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 DU MONT

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	—
Heater Current	600 mA	—
Focusing Method	Electrostatic text	—
Deflection Method	Electrostatic text	—
Phosphor	P2 text	—
Fluorescence	Blue-green/green text	—
Persistence	Long text	—
Post-Acceleration	Present text	—