



ELECTRONIC TUBE REFERENCE

3KP16

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

CATHODERAY

Three-inch electrostatically focused and deflected oscilloscope CRT with a P16 violet/near-ultraviolet screen of extremely short persistence. Sylvania and RCA data give anode capability to approximately 2.75 kV.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	2750 V
<i>CRT-specific electrode voltages, deflection factors, capacitances, focus/cutoff data, and other published electrical values are stored as section parameters because the promoted section columns are primarily conventional valve fields.</i>	

Sylvania 3KP16 direct-view oscilloscope CRT with electrostatic focus/deflection; P16 violet/near-UV, extremely short persistence. Published maximum ratings, capacitances, and typical operating conditions were extracted from the supplied datasheet.



SOURCE OPERATING CONDITIONS

1950 Sylvania

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1950 SYLVANIA

Section 1 · Cathode Ray

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Phosphor	P16	—
Focusing Method	Electrostatic	—
Deflecting Method	Electrostatic	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum Anode No. 2 Voltage	2750 V	—
Typical Anode No. 2 Voltage	2000 V	—



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1965 Sylvania Electronic Tubes Vol3

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1965 SYLVANIA ELECTRONIC TUBES VOL3

Section 1 · Cathode Ray

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	—
Heater Current	600 mA	—
FocusingMethod	Electrostatic	—
DeflectionMethod	Electrostatic	—

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Phosphor	P16 violet/near-UV, extremely short persistence	—
MinimumUsefulScreen	2.75 in	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Anode2VoltageMaximum	2750 V	—
Anode1FocusVoltageMaximum	1100 V	—
GridNegativeBiasMagnitudeMaximum	200 V	—
GridPositivePeakVoltageMaximum	2 V	—
PeakHeaterCathodeVoltageNegative	140 V	—
PeakVoltageAnode2ToDeflectionPlate	550 V	—
Anode2Voltage	2000 V	—
Anode1VoltageForFocus	320-600 V	—
GridVoltageForCutoff	-38 to -90 V	—
DeflectionFactorPlates1_2	100-136 V/in	—
DeflectionFactorPlates3_4	76-104 V/in	—
GridCircuitResistanceMaximum	1.5 Mohm	—
DeflectionCircuitResistanceMaximum	5 Mohm	—
Anode2PowerInputMaximum	6 W	—



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1971 RCA HB3 Binder 1 of 7

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1971 RCA HB3 BINDER 1 OF 7

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
In general , operation of the 3KP16 at an	3 V	Published CRT datasheet value; where a source row has several numbers they represent its separate limits or operating conditions.

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker