

ELECTRONIC TUBE REFERENCE

3UP7

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Three-inch cathode-ray tube for oscilloscope and instrument display service, using electrostatic focusing and electrostatic deflection. Its P7 screen designation identifies the phosphor variant within this compact oscillographic family.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	4000 V
Published ratings and characteristics promoted where clearly stated; identical repeated sections compressed when applicable.	

Printed companion 3UP-series cathode-ray designation on the same oscilloscope CRT source sheet.

SOURCE OPERATING CONDITIONS

1938 Raytheon

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1938 RAYTHEON

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater or filament voltage	6.3 V	Published nominal value
Heater or filament current	600 mA	Published nominal value