



ELECTRONIC TUBE REFERENCE

41MHL

Voltage - Triode (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Directly heated or receiving triode documented by the manufacturer; available source material does not establish a narrower functional category strongly enough for reassignment.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	4
NOMINAL HEATER	4 V / 1 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
PLATE RESISTANCE	11500 Ω
TRANSCONDUCTANCE	0.0045 S
AMPLIFICATION FACTOR	52
MAXIMUM PLATE VOLTAGE	200 V
Published ratings and characteristics promoted from approved datasheet.	

Cossor 41MHL triode for receiver/amplifier service as specified in the supplied catalogue datasheet.

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker