



ELECTRONIC TUBE REFERENCE

41MP

Voltage - Triode (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Directly heated or receiving triode documented by the manufacturer; available source material does not establish a narrower functional category strongly enough for reassignment.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	4
NOMINAL HEATER	4 V / 1 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
PLATE RESISTANCE	2500 Ω
TRANSCONDUCTANCE	0.0075 S
AMPLIFICATION FACTOR	18.7
MAXIMUM PLATE VOLTAGE	200 V
Published ratings and characteristics promoted from approved datasheet.	

Cossor 41MP triode for receiver/amplifier service as specified in the supplied catalogue datasheet.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

193X Cossor

Published test conditions and operating points. Values on this page are preserved as reported by this source.

193X COSSOR

Section 1 · Triode

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Optimum load	3000 ohm	Published datasheet value

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker