



ELECTRONIC TUBE REFERENCE

41MXP

Voltage - Triode (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Directly heated or receiving triode documented by the manufacturer; available source material does not establish a narrower functional category strongly enough for reassignment.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	4
NOMINAL HEATER	4 V / 1 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
PLATE RESISTANCE	1500 Ω
TRANSCONDUCTANCE	0.0075 S
AMPLIFICATION FACTOR	11.2
MAXIMUM PLATE VOLTAGE	200 V
Published ratings and characteristics promoted from approved datasheet.	

Cossor 41MXP triode for receiver/amplifier service as specified in the supplied catalogue datasheet.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

193X Cossor

Published test conditions and operating points. Values on this page are preserved as reported by this source.

193X COSSOR

Section 1 · Triode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Optimum load	2000 ohm	Published datasheet value