

ELECTRONIC TUBE REFERENCE

432B

Voltage Regulator electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

VOLTAGEREGULATOR

Three-electrode inert-gas cold-cathode reference tube with starting element, designed for stable approximately 100 V service over its operating range.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	4
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Indirect; cold cathode	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Voltage Regulator	
MAXIMUM CATHODE CURRENT	8 mA
REGULATOR VOLTAGE	100 V
MINIMUM REGULATOR CURRENT	4 mA
MAXIMUM REGULATOR CURRENT	8 mA
STARTING VOLTAGE	160 V
MAINTAINING VOLTAGE	100 V
Regulator values promoted from published cathode-current and anode breakdown/voltage-drop data.	

Western Electric 432B is a Three-electrode inert-gas-filled cold-cathode voltage-reference tube with starting element and stable voltage drop.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

2026 Western Electric 400s

Published test conditions and operating points. Values on this page are preserved as reported by this source.

2026 WESTERN ELECTRIC 400S

Section 1 · Voltage Regulator

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Regulation maximum	0.75 V	4to6mA
Starter breakdown voltage	200 V	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker