



ELECTRONIC TUBE REFERENCE

45M

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Power triode documented for amplifier or control service, with manufacturer operating data emphasizing useful power output rather than small-signal voltage amplification. Its available documentation does not justify a narrower specialized functional category.

GENERAL CHARACTERISTICS

BASE DESIGNATION	UX4	BASE PINS	—
NOMINAL HEATER	2.5 V / 1.5 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
PLATE RESISTANCE	1750 Ω
TRANSCONDUCTANCE	0.002 S
AMPLIFICATION FACTOR	3.5
MAXIMUM PLATE VOLTAGE	300 V
MAXIMUM PLATE DISSIPATION	11 W
MAXIMUM CATHODE CURRENT	45 mA

Mesh-plate Type 45 variant; source directs general electrical data to EML45. The supplied Emission Labs sheet was read for filament data, maximum ratings, representative operating points, gm/rp/mu, output conditions, capacitances, and rectifier filter conditions as applicable.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

2026 Emission Labs

Published test conditions and operating points. Values on this page are preserved as reported by this source.

2026 EMISSION LABS

Section 1 · Triode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Filament voltage	2.5 V	—
Filament current	1.5 A	—
Plate resistance	1750 ohm	ClassA
Amplification factor	3.5	ClassA
Transconductance	2000 uS	ClassA

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate voltage	250 V	ClassA
Plate current	34 mA	ClassA
Grid voltage	-50 V	ClassA
Load resistance	3900 ohm	ClassA
Output power	1.6 W	ClassA
Maximum Class A output power	2.5 W	—
Electrical data reference	45	SourceCrossReference

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker