

ELECTRONIC TUBE REFERENCE

4C36

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
TRIODE

Thoriated-tungsten high-power triode.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	5 V / 7.3 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
MAXIMUM PLATE VOLTAGE	4000 V
MAXIMUM PLATE DISSIPATION	125 W



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

9999 Mixed D 1000

Published test conditions and operating points. Values on this page are preserved as reported by this source.

9999 MIXED D 1000

Section 1 · Triode

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Current	7.3 A	—
Heater Voltage	5 V	—

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum Plate Dissipation	125 W	Class B audio and Class C RF ratings

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker