



ELECTRONIC TUBE REFERENCE

4CPX250K

Power - Beam (NOT sweep) (over 1000V 100W) electronic tube

CONSOLIDATED TECHNICAL
DATA

1 SECTION
CONSTRUCTION
BEAMPOWER

Compact forced-air-cooled external-anode radial-beam tetrode designed for wideband grid-pulsed RF amplification and pulse-modulator service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6 V / 2.5 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Beam Power	
AMPLIFICATION FACTOR	5
MAXIMUM PLATE VOLTAGE	7000 V
MAXIMUM SCREEN VOLTAGE	1000 V
MAXIMUM PLATE DISSIPATION	250 W
MAXIMUM SCREEN DISSIPATION	12 W
MAXIMUM GRID DISSIPATION	2 W
MAXIMUM CATHODE CURRENT	6 A

The EIMAC 8590/4CPX250K is a compact forced-air-cooled external-anode radial-beam tetrode for wideband grid-pulsed RF amplifier and pulse-modulator service.

SOURCE OPERATING CONDITIONS

1962 Eimac

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1962 EIMAC

Section 1 · Beam Power

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
CW Maximum Plate Voltage	2500 V	CW
Pulse RF Maximum Plate Voltage	5500 V	GridPulsed