

ELECTRONIC TUBE REFERENCE

4J32

Specialized - Magnetron electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

MAGNETRON

Fixed-frequency S-band pulse magnetron covering approximately 2.82-2.86 GHz for pulsed microwave oscillator applications.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	16 V / 3.1 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Magnetron	
MAXIMUM PLATE VOLTAGE	30000 V

Fixed-frequency S-band pulse magnetron covering 2820 to 2860 MHz.

SOURCE OPERATING CONDITIONS

1971 English Electric Valve

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1971 ENGLISH ELECTRIC VALVE

Section 1 · Magnetron

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Frequency range	2820–2860 MHz	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Typical peak output power	1000 kW	Pulse
Maximum peak anode voltage	30 kV	Pulse
Heater voltage	16 V	—
Heater current	3.1 A	—
Minimum cathode heating time	2 min	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker