

ELECTRONIC TUBE REFERENCE

4XP

Voltage - Triode (single) electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
TRIODE

Cossor directly heated triode for receiver and amplifier service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	4 V / 1 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
PLATE RESISTANCE	900 Ω
TRANSCONDUCTANCE	0.007 S
AMPLIFICATION FACTOR	6.3
MAXIMUM PLATE VOLTAGE	250 V
Published ratings and characteristics promoted from approved datasheet.	

Cossor 4XP triode for receiver/amplifier service as specified in the supplied catalogue datasheet.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1936 Cossor Valve Manual

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1936 COSSOR VALVE MANUAL

Section 1 · Triode

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Optimum load	3000 ohm	Published datasheet value

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker