



ELECTRONIC TUBE REFERENCE

5534

Specialized - X-Ray Tube electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

XRAY

Air-cooled Westinghouse diagnostic X-ray tube with a 4.2 mm focal spot and approximately 100 kV peak plate-voltage capability.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 XRay	
MAXIMUM PLATE VOLTAGE	100000 V
<i>Published ratings and characteristics promoted where clearly applicable; additional source values retained as section parameters.</i>	

Westinghouse X-ray tube with 4.2 mm focal spot specification for diagnostic/fluoroscopic high-voltage service.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1947 Westinghouse

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1947 WESTINGHOUSE

Section 1 · XRay

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Filament voltage range	3.5–10 V	Published
Filament current range	3.5 A–5.5 A	Published
Cooling	Air	Published
Focal spot size	4.2 mm	Projected size

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heat capacity	150000 heat unit	Published
Continuous rating	12000 heat unit/min	Published
Peak plate voltage	100 kV	Highest published full-wave/self-rectified value

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker