

ELECTRONIC TUBE REFERENCE

5645

Voltage - Triode (single) electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
TRIODE

Subminiature medium-mu triode for compact electronic equipment.

GENERAL CHARACTERISTICS

BASE DESIGNATION	5645	BASE PINS	5
NOMINAL HEATER	6.3 V / 150 mA	PARALLEL HEATER	– / –
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
PLATE RESISTANCE	7400 Ω
TRANSCONDUCTANCE	0.0027 S
AMPLIFICATION FACTOR	20
MAXIMUM PLATE VOLTAGE	150 V
MAXIMUM PLATE DISSIPATION	1 W
Medium-mu Class A triode.	

Subminiature medium-mu triode for compact equipment.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1950 Sylvania

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1950 SYLVANIA

Section 1 · Triode

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
HeaterOrFilamentVoltage	6.3 V	—
HeaterOrFilamentCurrent	150 mA	—



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

195X General Electric Essential Characteristics

Published test conditions and operating points. Values on this page are preserved as reported by this source.

195X GENERAL ELECTRIC ESSENTIAL CHARACTERISTICS

Section 1 · Triode

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Input Capacitance	2.2 pF	—
Output Capacitance	3 pF	—
Grid-to-Plate Capacitance	1.7 pF	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate Voltage	100 V	ClassA
Cathode Resistor	560 ohm	ClassA
Plate Current	5 mA	ClassA