

ELECTRONIC TUBE REFERENCE

56859

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Instrument or monochrome display cathode-ray tube for oscilloscope, monitor, or display service. The record identifies alternate designation D14376GH123 and high-voltage anode capability around 14 kV.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 100 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	14000 V

Instrument or monochrome display cathode-ray tube for oscilloscope, monitor, or display applications. Published phosphor: type. Explicit alternate designation printed with D14376GH123.

SOURCE OPERATING CONDITIONS

2004 PDS CRT Heerlen

Published test conditions and operating points. Values on this page are preserved as reported by this source.

2004 PDS CRT HEERLEN

Section 1 · Cathode Ray

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater voltage	6.3 V	—
Heater current	100 mA	—
Maximum anode/final accelerator voltage	14000 V	—
First accelerator voltage	2 kV	—

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Phosphor	type	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker