



ELECTRONIC TUBE REFERENCE

5762A

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	12.6 V / 29 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
AMPLIFICATION FACTOR	29
MAXIMUM PLATE VOLTAGE	6200 V
MAXIMUM PLATE DISSIPATION	4000 W



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

9999 Mixed H 1000

Published test conditions and operating points. Values on this page are preserved as reported by this source.

9999 MIXED H 1000

Section 1 · Triode

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Grid To Plate Capacitance	18 pF	—
Input Capacitance	19 pF	—
Output Capacitance	0.5 pF	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker