



ELECTRONIC TUBE REFERENCE

5923200A3

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	10 V / 5 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
TRANSCONDUCTANCE	0.0036 S
AMPLIFICATION FACTOR	25
MAXIMUM PLATE VOLTAGE	3500 V
MAXIMUM PLATE DISSIPATION	200 W
MAXIMUM GRID DISSIPATION	25 W



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1950 Eimac Tubes

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1950 EIMAC TUBES

Section 1 · Triode

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Grid To Plate Capacitance	3.3 pF	—
Input Capacitance	3.6 pF	—
Output Capacitance	0.29 pF	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker