

Five-inch high-resolution CRT with magnetic focusing and deflection, designed for flying-spot scanning, precision radar, and photographic applications. Its fine-resolution display system supports demanding image-generation and recording work.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray
No fixed ratings recorded.
CRT electron-gun/display section; CRT-specific ratings and operating data are stored as parameters.

High-resolution magnetic-focus and magnetic-deflection cathode-ray tube for flying-spot scanning, precision radar, and photographic applications.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1960 Du Mont

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 DU MONT

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Focusing method	1 code	Magnetic
Deflection method	1 code	Magnetic

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Accelerator voltage maximum	20000 V	—
Accelerator voltage	20000 V	—
Grid No. 1 voltage	—	Published range -110 to -35 V
Grid No. 1 negative bias maximum	200 V	—
X-ray shielding threshold	16000 V	Shielding may be necessary above this accelerator voltage
Grid No. 2 voltage	1000 V	—
Focusing coil current	135 mA	Approximate

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker