

Five-inch P1 cathode-ray instrument tube for oscillograph or measurement display, with manufacturer-specified focusing, deflection, accelerating voltages, and phosphor characteristics for precision waveform presentation.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 300 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	8000 V
Published DuMont/RMA/JEDEC ratings and characteristics promoted where applicable; additional display or photomultiplier data retained as parameters.	

Five-inch single-beam CRT with electrostatic focus/deflection, asymmetric scan, beam gating, and pattern/astigmatism adjustment.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1960 Du Mont

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 DU MONT

Section 1 · Cathode Ray

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Focusing method	Electrostatic	—
Deflection method	Electrostatic	—
Scan vertical	6 cm	—
Scan horizontal	10 cm	—

APPLICATION

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	Oscillographic / instrumentation display	—

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Post-accelerator voltage maximum	8000 V	—