

ELECTRONIC TUBE REFERENCE

6029

Voltage - Triode (single high frequency) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Directly heated subminiature triode for high-frequency oscillator service to several hundred megahertz.

GENERAL CHARACTERISTICS

BASE DESIGNATION	5677	BASE PINS	–
NOMINAL HEATER	1.25 V / 200 mA	PARALLEL HEATER	– / –
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
PLATE RESISTANCE	4250 Ω
TRANSCONDUCTANCE	0.002 S
AMPLIFICATION FACTOR	8.5
MAXIMUM PLATE VOLTAGE	135 V
Directly heated subminiature medium-mu triode.	

Directly heated subminiature triode for high-frequency oscillator service to several hundred megacycles.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1938 Raytheon

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1938 RAYTHEON

Section 1 · Triode

APPLICATION

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	HighFrequency_Oscillator text	—



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

195X General Electric Essential Characteristics

Published test conditions and operating points. Values on this page are preserved as reported by this source.

195X GENERAL ELECTRIC ESSENTIAL CHARACTERISTICS

Section 1 · Triode

CHARACTERISTIC

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Input capacitance	1.3 pF	—
Output capacitance	1.4 pF	—
Grid-to-plate capacitance	1.6 pF	—

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate voltage	90 V	ClassA
Control-grid bias	-4 V	ClassA
Plate current	11 mA	ClassA
Plate resistance	4250 ohm	ClassA

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Transconductance	2000 μ S	ClassA
Amplification factor	8.5	ClassA

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker