ELECTRONIC TUBE REFERENCE

6112

Voltage - Dual Triode (similar high frequency) electronic tube

CONSOLIDATED TECHNICAL DATA
2 SECTIONS
CONSTRUCTION
TRIODE-TRIODE

Subminiature high-mu twin triode intended for UHF amplifier service, offering two compact voltage-amplifying sections for high-frequency equipment.

General characteristics

BASE DESIGNATION	8DG	**BASE PINS**	8
NOMINAL HEATER	6.3 V / 300 mA	**PARALLEL HEATER**	— / —
HEATING	Indirect	**SERIES OPERATION**	Not specified
CATHODE ARRANGEMENT	Separate cathodes	**SECTION CONSTRUCTION**	Similar

8DG - Terminal pinout

TERMINAL	SECTION	ELEMENT	STATUS
PIN1 — 2P	B	P — Plate (Anode)	CONNECTED
PIN2 — 2G1	B	G1 — Control Grid	CONNECTED
PIN3 — H	—	H — Heater	CONNECTED
PIN4 — 2K	B	K — Cathode	CONNECTED
PIN5 — 1K	A	K — Cathode	CONNECTED
PIN6 — H	—	H — Heater	CONNECTED
PIN7 — 1G1	A	G1 — Control Grid	CONNECTED
PIN8 — 1P	A	P — Plate (Anode)	CONNECTED

Section ratings

SECTION1 Triode	
PLATE RESISTANCE	28000 Ω
TRANSCONDUCTANCE	0.0018 S
AMPLIFICATION FACTOR	70
MAXIMUM PLATE VOLTAGE	165 V
MAXIMUM PLATE DISSIPATION	0.1 W
MAXIMUM CATHODE CURRENT	22 mA
Representative row for electrically identical repeated sections.	

SECTION2 Triode	
PLATE RESISTANCE	28000 Ω
TRANSCONDUCTANCE	0.0018 S
AMPLIFICATION FACTOR	70
MAXIMUM PLATE VOLTAGE	165 V
MAXIMUM PLATE DISSIPATION	0.1 W
MAXIMUM CATHODE CURRENT	22 mA
Second physical triode restored under current one-row-per-physical-section policy.	

> Subminiature high-mu twin triode for UHF service.

SOURCE OPERATING CONDITIONS

1950 Sylvania

SOURCE PDF

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1950 SYLVANIA

Section 1 · Triode

CHARACTERISTIC		
PARAMETER	**PUBLISHED VALUE**	**CONDITION / NOTE**
Heater Voltage	**6.3 V**	—
Heater Current	**300 mA**	—

SOURCE DATA APPENDIX

SOURCE OPERATING CONDITIONS

195X General Electric Essential Characteristics

SOURCE PDF

Published test conditions and operating points. Values on this page are preserved as reported by this source.

195X GENERAL ELECTRIC ESSENTIAL CHARACTERISTICS

Section 1 · Triode

OTHER		
PARAMETER	**PUBLISHED VALUE**	**CONDITION / NOTE**
Maximum plate voltage	**165 V**	Published handbook rating
Plate voltage	**150 V**	ClassA
Plate current	**1.75 mA**	ClassA
Alternate plate voltage	**100 V**	ClassA OperatingPoint2
Alternate plate current	**0.8 mA**	ClassA OperatingPoint2

CHARACTERISTIC		
PARAMETER	**PUBLISHED VALUE**	**CONDITION / NOTE**
Plate resistance	**28000 ohm**	Published handbook characteristic

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Transconductance	**2500 µS**	Published handbook characteristic
Amplification factor	**70**	Published handbook characteristic
Heater/filament voltage	**6.3 V**	Published heater/filament rating
Heater/filament current	**300 mA**	Published heater/filament rating
Alternate plate resistance	**39000 ohm**	ClassA OperatingPoint2
Alternate transconductance	**1800 µS**	ClassA OperatingPoint2
Alternate amplification factor	**70**	ClassA OperatingPoint2

SOURCE OPERATING CONDITIONS

SOURCE PDF

1960 RCA Industrial and Communications Types

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 RCA INDUSTRIAL AND COMMUNICATIONS TYPES

Section 1 · Triode

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	**6.3 V**	—
Heater Current	**300 mA**	—

SOURCE DATA APPENDIX

SOURCE OPERATING CONDITIONS

SOURCE PDF

1961 Tung Sol

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1961 TUNG SOL

Section 1 · Triode

OTHER		
PARAMETER	**PUBLISHED VALUE**	**CONDITION / NOTE**
ImpactAcceleration	**450 g**	—
UniformAcceleration	**1000 g**	—
VibrationalAcceleration	**2.5 g**	—
Service	**UHF amplifier**	—

SOURCE OPERATING CONDITIONS

SOURCE PDF

1966 Tung Sol Electronic Tubes 4 of 4

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1966 TUNG SOL ELECTRONIC TUBES 4 OF 4
Section 1 · Triode

OTHER		
PARAMETER	**PUBLISHED VALUE**	**CONDITION / NOTE**
Heater/filament voltage	**6.3 V**	—
Heater/filament current	**300 mA**	—

APPLICATION		
PARAMETER	**PUBLISHED VALUE**	**CONDITION / NOTE**
Application summary	**Subminiature high-mu twin triode for UHF service.**	—

CHARACTERISTIC		
PARAMETER	**PUBLISHED VALUE**	**CONDITION / NOTE**
Plate voltage	**150 V**	—
Plate current	**8 mA**	—
Transconductance	**6000 uS**	—
Amplification factor	**60**	—
Grid-to-plate capacitance	**1.4 pF**	—
Maximum cathode current	**22 mA**	—

SOURCE OPERATING CONDITIONS

1999 Philips 0-D

SOURCE PDF

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1999 PHILIPS 0-D

Section 1 · Triode

OTHER		
PARAMETER	**PUBLISHED VALUE**	**CONDITION / NOTE**
Anode current	**0.8 mA**	Typical per section
Anode-grid capacitance	**1 pF**	Interelectrode
Grid-cathode-heater capacitance	**1.7 pF**	Interelectrode