

ELECTRONIC TUBE REFERENCE

6411

Specialized - Photo Tube electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

IMAGECONVERTERINTENSIFIER

Electrostatically focused image-converter tube designed to convert near-infrared images into visible phosphor-screen images.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 ImageConverterIntensifier
No fixed ratings recorded.
Image-converter electron-optical structure; published voltages and performance retained in parameters.

The ITT 6411 is a near-infrared image-converter tube with electrostatic focusing and p20 phosphor screen.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1962 ITT

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1962 ITT

Section 1 · ImageConverterIntensifier

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Cathode-to-anode voltage nominal	16000 V	—
Cathode-to-anode voltage maximum	16500 V	—
Focus voltage as percent of anode voltage	13–16 %	—
Maximum cathode current	2 uA	—
Cathode luminous sensitivity	12–25 uA/lm	—
Cathode radiant sensitivity at 8000 A	0.0012–0.0025 uA/uW	—
Phosphor screen luminous efficiency at 16 kV	30–55 lm/W	—
Infrared conversion index at 16 kV	10	—
Image magnification	0.66–0.7 x	—
Resolving power center	20 lp/mm	—

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Average cathode current density	0.4 uA/cm ²	—
Useful cathode diameter	0.97 in	—
Useful phosphor screen diameter	0.75 in	—

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker