

ELECTRONIC TUBE REFERENCE

6726

Diode (NOT rectifier) electronic tube

CONSOLIDATED TECHNICAL DATA

2 SECTIONS

CONSTRUCTION

DIODE-DIODE

Twin diode for detector, discriminator, clipping, and general signal rectification in receiving, communications, and general electronic equipment.

GENERAL CHARACTERISTICS

BASE DESIGNATION	6BT	BASE PINS	6
NOMINAL HEATER	6.3 V / 300 mA	PARALLEL HEATER	– / –
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

6BT - TERMINAL PINOUT

TERMINAL	SECTION	ELEMENT	STATUS
PIN1 – 1K	A	K – Cathode	CONNECTED
PIN2 – 2P	B	P – Plate (Anode)	CONNECTED
PIN3 – H	–	H – Heater	CONNECTED
PIN4 – H	–	H – Heater	CONNECTED
PIN5 – 2K	B	K – Cathode	CONNECTED
PIN6 – IS	A	IS – Internal Screen	CONNECTED
PIN7 – 1P	A	P – Plate (Anode)	CONNECTED

SECTION RATINGS

SECTION1 Diode	
PEAK INVERSE VOLTAGE	330 V
NOMINAL OUTPUT CURRENT	9 mA
PEAK FORWARD CURRENT	54 mA
FORWARD VOLTAGE DROP	10 V
<i>Published maximum ratings, representative operating conditions, and available capacitance/rectifier data reviewed.</i>	

SECTION2 Diode	
<i>No fixed ratings recorded.</i>	
<i>Physical second diode section added during approved section-structure reconciliation.</i>	

6726 is listed in the supplied receiving-tube handbook as a twin diode. The published heater/filament rating is 6.3 V at 0.30 A. Maximum ratings, representative operating characteristics, and available special-service data were captured from the supplied table.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

195X General Electric Essential Characteristics

Published test conditions and operating points. Values on this page are preserved as reported by this source.

195X GENERAL ELECTRIC ESSENTIAL CHARACTERISTICS

Section 1 · Diode

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater/filament voltage	6.3 V	Published heater/filament rating
Heater/filament current	300 mA	Published heater/filament rating
Tube voltage drop	10 V	At 60 mA DC

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
DC output current per plate	9 mA	HalfWave
Peak inverse voltage	330 V	HalfWave
RMS supply voltage per plate	117 V	HalfWave
Peak current per plate	54 mA	HalfWave

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker