



ELECTRONIC TUBE REFERENCE

6A8G

Voltage - Radio Detector Converter electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

HEPTODE

Glass-envelope pentagrid oscillator-converter for superheterodyne radio receivers. It combines local oscillation and mixing within one multi-grid tube, providing established frequency-changing performance from conventional receiver supplies.

GENERAL CHARACTERISTICS

BASE DESIGNATION	8A	BASE PINS	8
NOMINAL HEATER	6.3 V / 300 mA	PARALLEL HEATER	– / –
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Heptode	
PLATE RESISTANCE	360000 Ω
TRANSCONDUCTANCE	0.00055 S
MAXIMUM PLATE VOLTAGE	300 V
MAXIMUM SCREEN VOLTAGE	100 V
MAXIMUM PLATE DISSIPATION	1 W
MAXIMUM SCREEN DISSIPATION	0.3 W
MAXIMUM CATHODE CURRENT	14 mA
<i>Published maximum ratings and representative operating characteristics reviewed.</i>	

6A8G is explicitly printed with 6A8 on the same source and is a pentagrid frequency-converter designation covered by that sheet.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1937 Raytheon Radio Receiving Tubes

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1937 RAYTHEON RADIO RECEIVING TUBES

Section 1 · Heptode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate voltage	100 V	Converter
Screen voltage	50 V	Converter
Plate voltage	250 V	Converter
Screen voltage	100 V	Converter
Oscillator-grid resistor	50000 Ω	Converter

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Conversion transconductance	360 μS	Converter
Plate resistance	300000 Ω	Converter
Conversion transconductance	550 μS	Converter



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1948 Brimar Radio Valve Manual

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1948 BRIMAR RADIO VALVE MANUAL

Section 1 · Heptode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Oscillator Anode Voltage Maximum	200 V	G2

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum Operating Frequency	20 MHz	Suitable circuits


SOURCE DATA APPENDIX

SOURCE OPERATING CONDITIONS

1950 Sylvania

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1950 SYLVANIA

Section 1 · Heptode

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Transconductance	550 μ S	—
Conversion Transconductance	550 μ S	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum Plate Voltage	300 V	—


SOURCE DATA APPENDIX

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1958 Brimar Radio Valve No 7

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1958 BRIMAR RADIO VALVE NO 7

Section 1 · Heptode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate Voltage	250 V	—
Plate Current	3.5 mA	—
Screen Voltage	100 V	—

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Screen Current	2.7 mA	—
Oscillator Anode Supply Voltage	250 V	—



SOURCE DATA APPENDIX

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

195X General Electric Essential Characteristics

Published test conditions and operating points. Values on this page are preserved as reported by this source.

195X GENERAL ELECTRIC ESSENTIAL CHARACTERISTICS

Section 1 · Heptode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum plate voltage	300 V	Published handbook rating
Maximum screen voltage	100 V	Published handbook rating
Plate voltage	250 V	ClassA
Screen voltage	100 V	ClassA
Control-grid bias	3 V	ClassA
Plate current	3.5 mA	ClassA
Screen current	2.7 mA	ClassA

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate resistance	360000 ohm	Published handbook characteristic
Transconductance	550 μ S	Published handbook characteristic
Heater/filament voltage	6.3 V	Published heater/filament rating
Heater/filament current	300 mA	Published heater/filament rating

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

