



ELECTRONIC TUBE REFERENCE

6EV5CATV

Voltage - Tetrode electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TETRODE

Ericsson 6EV5/CATV long-life miniature seven-pin sharp-cutoff RF tetrode for dependable cable television distribution amplifiers, specially developed from the 6EV5 for extended CATV service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	7
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Tetrode

No fixed ratings recorded.

Ericsson 6EV5/CATV long-life sharp-cutoff RF tetrode, special 7-pin small-button E7-1 variant developed for cable television amplifier service. Manufacturer describes shielded cold grid-to-plate, input and output capacitances, with external shield tied to cathode. Basing: pin 1 grid-1; pins 2 and 7 cathode/internal shield; pins 3 and 4 heater; pin 5 plate; pin 6 screen grid-2. Published typical operation and lifetime acceptance tables contain OCR-alignment problems, so numerical heater, maximum voltage/dissipation and gm/rp fields deliberately left unset rather than inferred. Manufacturer 125 V anode operating test condition exists but is not a confirmed absolute maximum.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1965 Ericsson Longlife

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1965 ERICSSON LONGLIFE

Section 1 · Tetrode

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate Voltage	125 V	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker