



ELECTRONIC TUBE REFERENCE

6J11PE

Voltage Pentode - Sharp Cutoff (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

PENTODE

High-frequency pentode designed for RF or wideband voltage amplification in radio-electronic equipment.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	9
NOMINAL HEATER	6.3 V / 440 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Pentode	
TRANSCONDUCTANCE	0.028 S
MAXIMUM PLATE VOLTAGE	150 V
MAXIMUM SCREEN VOLTAGE	150 V
MAXIMUM PLATE DISSIPATION	4.9 W
MAXIMUM SCREEN DISSIPATION	1.15 W
MAXIMUM CATHODE CURRENT	40 mA
<i>Promoted ratings and characteristics translated from the filename-designated Russian entry only.</i>	

The 6J11PE is a Russian extended-life high-transconductance high-frequency pentode for wideband amplification. The source entry was translated to English and processed independently from neighboring partial entries.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1981 Russian Tubes Katsnelson and Larionov

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1981 RUSSIAN TUBES KATSNELSON AND LARIONOV

Section 1 · Pentode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Guaranteed service life	5000 h	Published source value
Nominal heater voltage	6.3 V	Published source value
Nominal heater current	440 mA	Published source value
Transconductance	28000 μS	Published operating point