



ELECTRONIC TUBE REFERENCE

6J22P

Voltage - Pentode Sharp Cutoff (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
PENTODE

High-frequency pentode designed for RF or wideband voltage amplification in radio-electronic equipment.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 500 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Pentode	
PLATE RESISTANCE	6500 Ω
TRANSCONDUCTANCE	0.023 S
MAXIMUM PLATE VOLTAGE	200 V
MAXIMUM SCREEN VOLTAGE	200 V
MAXIMUM PLATE DISSIPATION	6 W
MAXIMUM SCREEN DISSIPATION	1.2 W
<i>Promoted ratings and characteristics translated from the filename-designated Russian entry only.</i>	

The 6J22P is a Russian high-transconductance cathode-grid pentode for wideband RF preamplification. The source entry was translated to English and processed independently from neighboring partial entries.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1981 Russian Tubes Katsnelson and Larionov

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1981 RUSSIAN TUBES KATSNELSON AND LARIONOV

Section 1 · Pentode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Guaranteed service life	1500 h	Published source value
Nominal heater voltage	6.3 V	Published source value
Nominal heater current	500 mA	Published source value
Transconductance	23000 μS	Published operating point
Plate resistance	6500 Ω	Published operating point

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker