



ELECTRONIC TUBE REFERENCE

6J23PE

Voltage - Pentode Sharp Cutoff (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

PENTODE

High-frequency pentode designed for RF or wideband voltage amplification in radio-electronic equipment.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 440 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Pentode	
PLATE RESISTANCE	36000 Ω
TRANSCONDUCTANCE	0.03 S
MAXIMUM PLATE VOLTAGE	150 V
MAXIMUM SCREEN VOLTAGE	150 V
MAXIMUM PLATE DISSIPATION	2.5 W
MAXIMUM SCREEN DISSIPATION	1.15 W
MAXIMUM CATHODE CURRENT	40 mA
<i>Promoted ratings and characteristics translated from the filename-designated Russian entry only.</i>	

The 6J23PE is a Russian extended-life dual-anode high-frequency pentode for wideband voltage amplification. The source entry was translated to English and processed independently from neighboring partial entries.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1981 Russian Tubes Katsnelson and Larionov

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1981 RUSSIAN TUBES KATSNELSON AND LARIONOV

Section 1 · Pentode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Guaranteed service life	3000 h	Published source value
Nominal heater voltage	6.3 V	Published source value
Nominal heater current	440 mA	Published source value
Transconductance	30000 μS	Published operating point
Plate resistance	36000 Ω	Published operating point

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker