



ELECTRONIC TUBE REFERENCE

6J2BV

Voltage Pentode - Sharp Cutoff (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
PENTODE

High-frequency pentode designed for RF or wideband voltage amplification in radio-electronic equipment.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 200 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Pentode	
TRANSCONDUCTANCE	0.00375 S
MAXIMUM PLATE VOLTAGE	150 V
MAXIMUM SCREEN VOLTAGE	125 V
MAXIMUM PLATE DISSIPATION	0.9 W
MAXIMUM SCREEN DISSIPATION	0.5 W
MAXIMUM CATHODE CURRENT	14 mA
<i>Promoted ratings and characteristics translated from the filename-designated Russian entry only.</i>	

The 6J2BV is a Russian ruggedized subminiature high-frequency pentode for RF voltage amplification. The source entry was translated to English and processed independently from neighboring partial entries.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1981 Russian Tubes Katsnelson and Larionov

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1981 RUSSIAN TUBES KATSNELSON AND LARIONOV

Section 1 · Pentode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Guaranteed service life	2000 h	Published source value
Nominal heater voltage	6.3 V	Published source value
Nominal heater current	200 mA	Published source value
Transconductance	3750 μS	Published operating point