

ELECTRONIC TUBE REFERENCE

6K1BV

Voltage - Pentode Remote Cutoff (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
PENTODE

Ruggedized Russian subminiature variable-mu pentode for dependable intermediate-frequency amplifier service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 200 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Pentode	
TRANSCONDUCTANCE	0.0036 S
MAXIMUM PLATE VOLTAGE	150 V
MAXIMUM SCREEN VOLTAGE	125 V
MAXIMUM PLATE DISSIPATION	1.2 W
MAXIMUM SCREEN DISSIPATION	0.4 W
MAXIMUM CATHODE CURRENT	15 mA
Promoted values translated from the complete filename-designated Russian entry only.	

The 6K1BV is a Russian ruggedized subminiature intermediate-frequency variable-mu pentode. The source entry was translated to English and processed independently from neighboring partial entries.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1981 Russian Tubes Katsnelson and Larionov

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1981 RUSSIAN TUBES KATSNELSON AND LARIONOV

Section 1 · Pentode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Nominal heater voltage	6.3 V	Published source value
Nominal heater current	200 mA	Published source value
Guaranteed service life	2000 h	Published source value
Transconductance	3600 μ S	Published operating point

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker