



ELECTRONIC TUBE REFERENCE

6P35GV

Power - Pentode Single (NOT beam) (under 10W) electronic tube

CONSOLIDATED TECHNICAL
DATA

1 SECTION
CONSTRUCTION
PENTODE

Power/output pentode designed for low-frequency or audio-frequency output amplification.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 450 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Pentode	
TRANSCONDUCTANCE	0.0105 S
MAXIMUM PLATE VOLTAGE	170 V
MAXIMUM SCREEN VOLTAGE	100 V
MAXIMUM PLATE DISSIPATION	5.2 W
MAXIMUM SCREEN DISSIPATION	0.8 W
MAXIMUM CATHODE CURRENT	75 mA
<i>Promoted ratings and characteristics translated from the filename-designated Russian entry only.</i>	

The 6P35GV is a Russian high-reliability low-frequency output pentode. Its Russian source entry was translated to English and processed independently from neighboring partial entries.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1981 Russian Tubes Katsnelson and Larionov

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1981 RUSSIAN TUBES KATSNELSON AND LARIONOV

Section 1 · Pentode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Nominal heater voltage	6.3 V	Published source value
Nominal heater current	450 mA	Published source value
Transconductance	10500 μ S	Published operating point
Guaranteed service life	500 h	Published source value

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker