



ELECTRONIC TUBE REFERENCE

6SR7GT

Voltage - Triode (with diode, heptode or hexode) electronic tube

CONSOLIDATED TECHNICAL
DATA

3 SECTIONS

CONSTRUCTION

DIODE-DIODE-TRIODE

Double-diode triode combining radio detector and AVC rectification with subsequent voltage amplification. The paired diodes handle signal and control-voltage functions while the triode provides receiver audio or voltage gain.

GENERAL CHARACTERISTICS

BASE DESIGNATION	80	BASE PINS	8
NOMINAL HEATER	6.3 V / 300 mA	PARALLEL HEATER	– / –
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Common cathode	SECTION CONSTRUCTION	Dissimilar

SECTION RATINGS

SECTION1 Diode

No fixed ratings recorded.

Representative of two identical diode sections.

SECTION2 Triode

PLATE RESISTANCE	8500 Ω
TRANSCONDUCTANCE	0.0019 S
AMPLIFICATION FACTOR	16
MAXIMUM PLATE VOLTAGE	250 V
<i>Medium-mu triode section.</i>	

SECTION3 Diode

No fixed ratings recorded.

Physical diode section added during approved section-structure reconciliation.

A heater-cathode duplex-diode/medium-mu triode. The two diode sections share the printed entry with a triode section characterized for Class-A voltage-amplifier service.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

195X General Electric Essential Characteristics

Published test conditions and operating points. Values on this page are preserved as reported by this source.

195X GENERAL ELECTRIC ESSENTIAL CHARACTERISTICS

Section 2 · Triode

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Input capacitance	3.6 pF	—
Output capacitance	2.8 pF	—
Grid-plate capacitance	2.4 pF	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate voltage	250 V	ClassA
Grid voltage	-9 V	ClassA
Plate current	9.5 mA	ClassA

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate resistance	8500 ohm	ClassA
Transconductance	1900 uS	ClassA
Amplification factor	16	ClassA