



ELECTRONIC TUBE REFERENCE

6V4P

Voltage - Pentode Sharp Cutoff (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

PENTODE

Russian small-signal pentode whose available source supports amplifier service but does not establish a narrower specialized application.

GENERAL CHARACTERISTICS

BASE DESIGNATION	B9A	BASE PINS	9
NOMINAL HEATER	– / –	PARALLEL HEATER	– / –
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Pentode	
MAXIMUM PLATE DISSIPATION	1.7 W
<i>Filename-matched Russian source entry only.</i>	

Russian pentode vacuum tube. Technical characteristics and ratings are taken from the complete filename-matched source entry.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1981 Russian Tubes Katsnelson and Larionov

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1981 RUSSIAN TUBES KATSNELSON AND LARIONOV

Section 1 · Pentode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater current	120320 mA	Translated from Russian source; Ток накала (120320) MA
Plate current	1235 mA	Translated from Russian source; Ток анода (1235) mA
Transconductance	-0.6 mA/V	Translated from Russian source; Крутизна характеристики , (1,9-0,6) mA/B
Output capacitance	0.35 pF	Translated from Russian source; ВЫХОДная , , . . . в в а в е , (2,65-0,35) пФ
Transconductance	1 mA/V	Translated from Russian source; крутизна характеристики , , , , , , 1 mA/B

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Service life	21000 h	Translated from Russian source; Нарботка , 21000 ч
Heater voltage	1.32 V	Translated from Russian source; Напряжение накала , 1,08—1,32
Plate voltage	150 V	Translated from Russian source; Напряжение анода з аеаа , 150 B
Plate dissipation	1.7 W	Translated from Russian source; Мощность, рассеиваемая анодом PE з,. 1,7 Вт

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

