



ELECTRONIC TUBE REFERENCE

6ZH23PE

Voltage - Pentode High Frequency (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

PENTODE

Russian indirectly heated voltage-amplifier pentode; typical anode 150 V, 14 mA; printed transconductance 30 Ma/V.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 440 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 0 Pentode	
TRANSCONDUCTANCE	0.03 S
Typical anode 150 V, current 0.014 A, datasheet anode power 2.45 W (not promoted as maximum); printed transconductance 30 Ma/V, units require validation.	

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

2026 Russian Receiving

Published test conditions and operating points. Values on this page are preserved as reported by this source.

2026 RUSSIAN RECEIVING

Section 0 · Pentode

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate Voltage	150 V	Typical anode voltage
5.5	14 mA	Typical anode current
8750	150 V	Typical screen-grid voltage

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater/filament voltage	6.3 V	Heater voltage
Heater/filament current	440 mA	Heater current

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker