

ELECTRONIC TUBE REFERENCE

7228

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Five-inch direct-view storage tube for radar, transient studies, data transmission, and visual display. It stores written information electronically for persistent, flicker-free observation.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	11000 V
Direct-view storage electron-beam system.	

Five-inch direct-view storage tube for radar, transient studies, data transmission and visual display.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1947 Westinghouse

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1947 WESTINGHOUSE

Section 1 · Cathode Ray

APPLICATION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	Radar_TransientStorage_DataTransmission text	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker