



ELECTRONIC TUBE REFERENCE

7545XD45

Power - Triode (over 1000V 100W) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Very-high-power pulse triode with published transmitting-class electrical ratings and operating data.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	10 V / 120 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
AMPLIFICATION FACTOR	30
MAXIMUM PLATE VOLTAGE	25000 V
MAXIMUM PLATE DISSIPATION	6000 W
PEAK FORWARD CURRENT	130 A
<i>Published ratings and characteristics promoted where applicable; remaining useful published values retained as parameters.</i>	

7545XD45: Central Electronic Manufacturers power/pulse triode with published electrical ratings and operating data. The complete approved datasheet was read semantically, including specifications, maximum ratings, operating conditions, cooling requirements and characteristic data where published.

SOURCE OPERATING CONDITIONS

195X Central Electronics

Published test conditions and operating points. Values on this page are preserved as reported by this source.

195X CENTRAL ELECTRONICS

Section 1 · Triode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Filament voltage	10 V	—
Filament current	120 A	—
Amplification factor	30	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum plate voltage	25000 V	—
Maximum plate/anode dissipation	6000 W	—
Maximum peak anode current	130 A	—
Maximum pulse cathode current	200 A	—
Maximum DC plate current	6 A	—
Maximum Class C input	48000 W	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker