



ELECTRONIC TUBE REFERENCE

7651

Power - Beam (NOT sweep) (over 1000V 100W) electronic tube

CONSOLIDATED TECHNICAL
DATA

1 SECTION
CONSTRUCTION
BEAMPOWER

High-power beam tetrode intended for audio-frequency output stages, combining substantial plate dissipation with high current capability for professional and hi-fi amplifiers.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 7.5 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Beam Power	
MAXIMUM PLATE VOLTAGE	5000 V
MAXIMUM SCREEN VOLTAGE	1200 V
MAXIMUM PLATE DISSIPATION	600 W
<i>Published ratings/characteristics promoted from supplied datasheet.</i>	

The 7651 is a beam-power transmitting tube. The supplied datasheet was processed for heater or filament data, maximum ratings, operating characteristics, capacitances where published, and service-specific power or frequency data.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1971 RCA HB3 Binder 6 of 7

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1971 RCA HB3 BINDER 6 OF 7

Section 1 · Beam Power

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum DC Plate Voltage	5000 V	Pulsed RF power service
Maximum DC Screen Voltage	1200 V	Pulsed RF power service
Maximum DC Plate Current During Pulse	9 A	Pulsed RF power service
Average Plate Dissipation	600 W	Pulsed RF power service
Peak Positive-Pulse Plate Voltage	10000 V	Pulsed RF power service
Typical DC Plate Voltage	4000 V	Pulsed RF power service
Typical Peak Useful Power Output	209 kW	Pulsed RF power service

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Mu Factor, Screen to Control Grid	13	Pulsed RF power service

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker