

ELECTRONIC TUBE REFERENCE

7730

Voltage - Dual Triode (similar) electronic tube

CONSOLIDATED TECHNICAL DATA

2 SECTIONS

CONSTRUCTION

TRIODE-TRIODE

High-reliability medium-mu twin triode for 12AU7-class service, providing two similar sections for dependable general-purpose voltage amplification and control circuitry.

GENERAL CHARACTERISTICS

BASE DESIGNATION	E9-1 / 9A	BASE PINS	9
NOMINAL HEATER	6.3 V / 300 mA	PARALLEL HEATER	6.3 V / 300 mA
HEATING	Indirect	SERIES OPERATION	Capable
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
PLATE RESISTANCE	7700 Ω
TRANSCONDUCTANCE	0.0022 S
AMPLIFICATION FACTOR	17
MAXIMUM PLATE VOLTAGE	330 V
MAXIMUM PLATE DISSIPATION	3 W
MAXIMUM CATHODE CURRENT	20 mA
Promoted from 250 V characteristic point; identical twin sections compressed.	

SECTION2 Triode	
PLATE RESISTANCE	7700 Ω
TRANSCONDUCTANCE	0.0022 S
AMPLIFICATION FACTOR	17
MAXIMUM PLATE VOLTAGE	330 V
MAXIMUM PLATE DISSIPATION	3 W
MAXIMUM CATHODE CURRENT	20 mA
Second identical physical triode section; added to align rows with SectionCount.	

Medium-mu twin triode, high-reliability replacement for 12AU7; identical sections compressed to one section row.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1960 CBS Hytron

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 CBS HYTRON

Section 1 · Triode

CAPACITANCE

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Grid-to-plate capacitance	1.5 pF	EachSection

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate voltage	100 V	ClassA

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate current	11.8 mA	V _a =100V
Transconductance	3100 μ S	V _a =100V
Plate resistance	6500 Ω m	V _a =100V

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker