

ELECTRONIC TUBE REFERENCE

7AUP4

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

CATHODERAY

Seven-inch P4 cathode-ray display tube with a white screen, using manufacturer-specified focusing and deflection characteristics for direct visual display in type 7AUP4.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 300 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	11000 V
Published ratings and characteristics promoted from the supplied datasheet where legible.	

Sylvania seven-inch CRT with electrostatic focus, magnetic deflection, and Aluminized P4 white, short-to-medium persistence. Published electrical ratings, capacitances, and operating conditions were extracted from the supplied datasheet.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1950 Sylvania

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1950 SYLVANIA

Section 1 · Cathode Ray

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	Nominal published value



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1965 Sylvania Electronic Tubes Vol3

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1965 SYLVANIA ELECTRONIC TUBES VOL3

Section 1 · Cathode Ray

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	—
Heater Current	300 mA	—
FocusingMethod	Electrostatic	—
DeflectionMethod	Magnetic	—
Deflection Angle	70 degree	—
Phosphor	Aluminized P4 white, short-to-medium persistence	—
MinimumUsefulScreen	6 in	—
Cathode To All Capacitance	7 pF	—
Grid1 To All Capacitance	9 pF	—

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Grid2 To All Capacitance	7 pF	—
LineWidth	0.012 in	BeamCurrent=50uA

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Grid1CircuitResistanceMaximum	1.5 Mohm	—
AnodeVoltageMaximum	11000 V	—
Grid4FocusVoltageMaximum	1100 V	—
Grid2VoltageMaximum	770 V	—
HeaterCathodeVoltageMaximum	450 V	Warmup<=15s;HeaterNegative
HeaterCathodeVoltageMaximum	200 V	AfterWarmup
Anode Voltage	8000 V	—
Grid4VoltageForFocus	0 to 300 V	—
Grid2 Voltage	300 V	—
Grid1VoltageForCutoff	-25 to -50 V	—
Grid2CircuitResistanceMaximum	10000 ohm	—
Grid4CircuitResistanceMaximum	10000 ohm	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker