



ELECTRONIC TUBE REFERENCE

7AYP25

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Seven-inch P25 cathode-ray instrument tube for oscillographic or measurement display, with manufacturer-specified focusing, deflection, accelerating-voltage, and phosphor characteristics.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	16000 V
<i>Published Sylvania CRT voltage ratings, capacitances, focusing/deflection, and typical operating conditions extracted.</i>	

Sylvania seven-inch CRT with electrostatic focus, electrostatic deflection, and P25 orange, medium persistence. Published electrical ratings, capacitances, and operating conditions were extracted from the supplied datasheet.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1965 Sylvania Electronic Tubes Vol3

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1965 SYLVANIA ELECTRONIC TUBES VOL3

Section 1 · Cathode Ray

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	—
Heater Current	600 mA	—
FocusingMethod	Electrostatic	—
DeflectionMethod	Electrostatic	—
Phosphor	P25 orange, medium persistence	—
MinimumUsefulScreen	4.75 x 5.75 in	—
DeflectionFactorUniformityMaximum	3 %	—
LineWidthMaximum	0.3 mm	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Grid1CircuitResistanceMaximum	1.5 Mohm	—
PostAcceleratorVoltageMaximum	16000 V	—
AnodeVoltageMaximum	8000 V	—
PostAcceleratorToAnodeVoltageRatioMaximum	2	—
FocusElectrodeVoltageMaximum	2500 V	—
Grid1NegativeBiasMagnitudeMaximum	200 V	—
HeaterCathodeVoltageMaximum	180 V	—
PeakVoltageAnodeToDeflectionPlate	1500 V	—
PostAcceleratorVoltage	10000 V	—
Anode Voltage	5000 V	—
FocusElectrodeVoltage	1375 to 1875 V	—
Grid1VoltageForCutoff	-50 to -90 V	—

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
DeflectionFactorD1D2	125 to 150 V/in	—
DeflectionFactorD3D4	100 to 125 V/in	—
DeflectionCircuitResistanceMaximum	3 Mohm	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker