

ELECTRONIC TUBE REFERENCE

7C26

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
TRIODE

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	9 V / 28 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
TRANSCONDUCTANCE	0.02 S
AMPLIFICATION FACTOR	17
MAXIMUM PLATE VOLTAGE	3000 V
MAXIMUM PLATE DISSIPATION	1000 W



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

9999 Mixed D 1000

Published test conditions and operating points. Values on this page are preserved as reported by this source.

9999 MIXED D 1000

Section 1 · Triode

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Grid To Plate Capacitance	10 pF	—
Input Capacitance	11 pF	—
Output Capacitance	1 pF	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker