



ELECTRONIC TUBE REFERENCE

8005

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Transmitting power triode intended for RF amplifier and oscillator service, with manufacturer ratings emphasizing radio-frequency output, substantial plate loading, and professional transmitter operation.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	4
NOMINAL HEATER	10 V / 3.25 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
AMPLIFICATION FACTOR	20
MAXIMUM PLATE VOLTAGE	1500 V
MAXIMUM PLATE DISSIPATION	85 W
<i>Published source values promoted where applicable; additional published values retained as parameters.</i>	

The RCA 8005 is a thoriated-tungsten power triode for AF/RF service, with published push-pull RF output around 330 W.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1950 General Electric Transmitting Types

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1950 GENERAL ELECTRIC TRANSMITTING TYPES

Section 1 · Triode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum full-rating frequency	60 MHz	—
Maximum signal power output	300 W	ClassB



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1956 RCA Transmitting Tubes

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1956 RCA TRANSMITTING TUBES

Section 1 · Triode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum Full-Input Frequency	60 MHz	—
Maximum Reduced-Input Frequency	100 MHz	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Push-Pull RF Power Output	330 W	PushPull; TwoTubes

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker