



ELECTRONIC TUBE REFERENCE

8025

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Power transmitting triode for RF amplification, oscillation, modulation, or related high-power electronic service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 1.92 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
AMPLIFICATION FACTOR	18
MAXIMUM PLATE VOLTAGE	1000 V
MAXIMUM PLATE DISSIPATION	40 W
<i>Published ratings and characteristics promoted from the approved RCA source.</i>	

UHF transmitting triode for high-frequency RF power service.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1940 RCA

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1940 RCA

Section 1 · Triode

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
RFPowerOutput	22 W	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker