

ELECTRONIC TUBE REFERENCE

8506

Power - Triode Single (under 10W) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Metal-ceramic planar UHF triode for radio-frequency power-amplifier service. Its high transconductance and amplification factor around 110 combine strong gain with extremely low plate-to-cathode capacitance in compact high-frequency circuitry.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 400 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
TRANSCONDUCTANCE	0.029 S
AMPLIFICATION FACTOR	110
MAXIMUM PLATE VOLTAGE	300 V
MAXIMUM PLATE DISSIPATION	5 W
MAXIMUM CATHODE CURRENT	40 mA
Promoted fields are used only where the published value maps cleanly to the locked schema; device-specific microwave, pulse, photoelectric, camera, and indicator data are preserved as parameter rows.	

Metal-ceramic planar UHF triode for radio-frequency power-amplifier service.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1964 RMA EIA

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1964 RMA EIA

Section 1 · Triode

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Grid-to-plate capacitance	2.5 pF	—
Grid-to-cathode capacitance	4.8 pF	—
Plate-to-cathode capacitance	0.025 pF	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate voltage maximum	300 V	—
Plate dissipation maximum	5 W	—
Grid current maximum	2 mA	—
Cathode current maximum	40 mA	—

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate voltage	200 V	—
Cathode resistor	40 0hm	—
Amplification factor	110 ratio	—
Transconductance	29000 uS	—
Plate current	25 mA	—
Grid voltage	-3.5 V	Ib=50uA

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker